



JDBC Tutorial

Tutorialspoint.com

The JDBC API is a Java API that can access any kind of tabular data, especially data stored in a Relational Database. JDBC stands for Java Database Connectivity.

JDBC works with Java on a variety of platforms, such as Windows, Mac OS, and the various versions of UNIX. This tutorial gives an initial push to start you with log4j. For more detail kindly check tutorialspoint.com/jdbc

What is JDBC?

JDBC stands for **J**ava **D**atabase **C**onnectivity, which is a standard Java API for database-independent connectivity between the Java programming language and a wide range of databases.

The JDBC library includes APIs for each of the tasks commonly associated with database usage:

- Making a connection to a database
- Creating SQL or MySQL statements
- Executing that SQL or MySQL queries in the database
- Viewing & Modifying the resulting records

Pre-Requisite:

You need to have good understanding on the following two subjects to learn JDBC:

1. [Core JAVA Programming](#)
2. [SQL or MySQL Database](#)

JDBC - Environment Setup:

Make sure you have done following setup:

1. Core JAVA Installation
2. SQL or MySQL Database Installation

Apart from the above you need to setup a database which you would use for your project. Assuming this is EMP and you have created on table Employees within the same database.

Creating JDBC Application:

There are six steps involved in building a JDBC application which I'm going to brief in this tutorial:

Import the packages:

This requires that you include the packages containing the JDBC classes needed for database programming. Most often, using `import java.sql.*` will suffice as follows:

```
//STEP 1. Import required packages
import java.sql.*;
```



Register the JDBC driver:

This requires that you initialize a driver so you can open a communications channel with the database. Following is the code snippet to achieve this:

```
//STEP 2: Register JDBC driver
Class.forName("com.mysql.jdbc.Driver");
```

Open a connection:

This requires using the `DriverManager.getConnection()` method to create a `Connection` object, which represents a physical connection with the database as follows:

```
//STEP 3: Open a connection
// Database credentials
static final String USER = "username";
static final String PASS = "password";
System.out.println("Connecting to database...");
conn = DriverManager.getConnection(DB_URL, USER, PASS);
```

Execute a query:

This requires using an object of type `Statement` or `PreparedStatement` for building and submitting an SQL statement to the database as follows:

```
//STEP 4: Execute a query
System.out.println("Creating statement...");
stmt = conn.createStatement();
String sql;
sql = "SELECT id, first, last, age FROM Employees";
ResultSet rs = stmt.executeQuery(sql);
```

If there is an SQL `UPDATE`, `INSERT` or `DELETE` statement required, then following code snippet would be required:

```
//STEP 4: Execute a query
System.out.println("Creating statement...");
stmt = conn.createStatement();
String sql;
sql = "DELETE FROM Employees";
ResultSet rs = stmt.executeUpdate(sql);
```

Extract data from result set:

This step is required in case you are fetching data from the database. You can use the appropriate `ResultSet.getXXX()` method to retrieve the data from the result set as follows:

```
//STEP 5: Extract data from result set
while(rs.next()){
    //Retrieve by column name
    int id = rs.getInt("id");
    int age = rs.getInt("age");
    String first = rs.getString("first");
    String last = rs.getString("last");
}
```

```
//Display values
System.out.print("ID: " + id);
System.out.print(", Age: " + age);
System.out.print(", First: " + first);
System.out.println(", Last: " + last);
}
```

Clean up the environment:

You should explicitly close all database resources versus relying on the JVM's garbage collection as follows:

```
//STEP 6: Clean-up environment
rs.close();
stmt.close();
conn.close();
```

JDBC Program:

Based on the above steps, we can have following consolidated sample code which we can use as a template while writing our JDBC code:

This sample code has been written based on the environment and database setup done in Environment chapter.

```
//STEP 1. Import required packages
import java.sql.*;

public class FirstExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/EMP";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
            Class.forName("com.mysql.jdbc.Driver");

            //STEP 3: Open a connection
            System.out.println("Connecting to database...");
            conn = DriverManager.getConnection(DB_URL,USER,PASS);

            //STEP 4: Execute a query
            System.out.println("Creating statement...");
            stmt = conn.createStatement();
            String sql;
            sql = "SELECT id, first, last, age FROM Employees";
            ResultSet rs = stmt.executeQuery(sql);

            //STEP 5: Extract data from result set
            while(rs.next()){
                //Retrieve by column name
```

```
int id = rs.getInt("id");
int age = rs.getInt("age");
String first = rs.getString("first");
String last = rs.getString("last");

//Display values
System.out.print("ID: " + id);
System.out.print(", Age: " + age);
System.out.print(", First: " + first);
System.out.println(", Last: " + last);
}
//STEP 6: Clean-up environment
rs.close();
stmt.close();
conn.close();
}catch(SQLException se){
    //Handle errors for JDBC
    se.printStackTrace();
}catch(Exception e){
    //Handle errors for Class.forName
    e.printStackTrace();
}finally{
    //finally block used to close resources
    try{
        if(stmt!=null)
            stmt.close();
    }catch(SQLException se2){
    }// nothing we can do
    try{
        if(conn!=null)
            conn.close();
    }catch(SQLException se){
        se.printStackTrace();
    }//end finally try
} //end try
System.out.println("Goodbye!");
} //end main
} //end FirstExample
```

Now let us compile above example as follows:

```
C:\>javac FirstExample.java
C:\>
```

When you run **FirstExample**, it produces following result:

```
C:\>java FirstExample
Connecting to database...
Creating statement...
ID: 100, Age: 18, First: Zara, Last: Ali
ID: 101, Age: 25, First: Mahnaz, Last: Fatma
ID: 102, Age: 30, First: Zaid, Last: Khan
ID: 103, Age: 28, First: Sumit, Last: Mittal
C:\>
```

SQLException Methods:

A SQLException can occur both in the driver and the database. When such an exception occurs, an object of type SQLException will be passed to the catch clause.

The passed SQLException object has the following methods available for retrieving additional information about the exception:

| Method | Description |
|--------------------------------|---|
| getErrorCode() | Gets the error number associated with the exception. |
| getMessage() | Gets the JDBC driver's error message for an error handled by the driver or gets the Oracle error number and message for a database error. |
| getSQLState() | Gets the XOPEN SQLstate string. For a JDBC driver error, no useful information is returned from this method. For a database error, the five-digit XOPEN SQLstate code is returned. This method can return null. |
| getNextException() | Gets the next Exception object in the exception chain. |
| printStackTrace() | Prints the current exception, or throwable, and its backtrace to a standard error stream. |
| printStackTrace(PrintStream s) | Prints this throwable and its backtrace to the print stream you specify. |
| printStackTrace(PrintWriter w) | Prints this throwable and its backtrace to the print writer you specify. |

By utilizing the information available from the Exception object, you can catch an exception and continue your program appropriately. Here is the general form of a try block:

```
try {
    // Your risky code goes between these curly braces!!!
}
catch(Exception ex) {
    // Your exception handling code goes between these
    // curly braces, similar to the exception clause
    // in a PL/SQL block.
}
finally {
    // Your must-always-be-executed code goes between these
    // curly braces. Like closing database connection.
}
```

JDBC - Data Types:

The following table summarizes the default JDBC data type that the Java data type is converted to when you call the setXXX() method of the PreparedStatement or CallableStatement object or the ResultSet.updateXXX() method.

| SQL | JDBC/Java | setXXX | updateXXX |
|-------------|----------------------|---------------|------------------|
| VARCHAR | java.lang.String | setString | updateString |
| CHAR | java.lang.String | setString | updateString |
| LONGVARCHAR | java.lang.String | setString | updateString |
| BIT | boolean | setBoolean | updateBoolean |
| NUMERIC | java.math.BigDecimal | setBigDecimal | updateBigDecimal |
| TINYINT | byte | setByte | updateByte |
| SMALLINT | short | setShort | updateShort |
| INTEGER | int | setInt | updateInt |
| BIGINT | long | setLong | updateLong |
| REAL | float | setFloat | updateFloat |
| FLOAT | float | setFloat | updateFloat |
| DOUBLE | double | setDouble | updateDouble |
| VARBINARY | byte[] | setBytes | updateBytes |
| BINARY | byte[] | setBytes | updateBytes |
| DATE | java.sql.Date | setDate | updateDate |
| TIME | java.sql.Time | setTime | updateTime |
| TIMESTAMP | java.sql.Timestamp | setTimestamp | updateTimestamp |
| CLOB | java.sql.Clob | setClob | updateClob |
| BLOB | java.sql.Blob | setBlob | updateBlob |

| | | | |
|--------|-----------------|-----------|--------------|
| ARRAY | java.sql.Array | setARRAY | updateARRAY |
| REF | java.sql.Ref | SetRef | updateRef |
| STRUCT | java.sql.Struct | SetStruct | updateStruct |

JDBC 3.0 has enhanced support for BLOB, CLOB, ARRAY, and REF data types. The ResultSet object now has updateBLOB(), updateCLOB(), updateArray(), and updateRef() methods that enable you to directly manipulate the respective data on the server.

The setXXX() and updateXXX() methods enable you to convert specific Java types to specific JDBC data types. The methods, setObject() and updateObject(), enable you to map almost any Java type to a JDBC data type.

ResultSet object provides corresponding getXXX() method for each data type to retrieve column value. Each method can be used with column name or by its ordinal position.

| SQL | JDBC/Java | setXXX | getXXX |
|-------------|----------------------|---------------|---------------|
| VARCHAR | java.lang.String | setString | getString |
| CHAR | java.lang.String | setString | getString |
| LONGVARCHAR | java.lang.String | setString | getString |
| BIT | boolean | setBoolean | getBoolean |
| NUMERIC | java.math.BigDecimal | setBigDecimal | getBigDecimal |
| TINYINT | byte | setByte | getByte |
| SMALLINT | short | setShort | getShort |
| INTEGER | int | setInt | getInt |
| BIGINT | long | setLong | getLong |
| REAL | float | setFloat | getFloat |
| FLOAT | float | setFloat | getFloat |
| DOUBLE | double | setDouble | getDouble |
| VARBINARY | byte[] | setBytes | getBytes |

| | | | |
|-----------|--------------------|--------------|--------------|
| BINARY | byte[] | setBytes | getBytes |
| DATE | java.sql.Date | setDate | getDate |
| TIME | java.sql.Time | setTime | getTime |
| TIMESTAMP | java.sql.Timestamp | setTimestamp | getTimestamp |
| CLOB | java.sql.Clob | setClob | getClob |
| BLOB | java.sql.Blob | setBlob | getBlob |
| ARRAY | java.sql.Array | setARRAY | getARRAY |
| REF | java.sql.Ref | SetRef | getRef |
| STRUCT | java.sql.Struct | SetStruct | getStruct |

JDBC - Create Database Example

This tutorial provides an example on how to create a Database using JDBC application. Before executing following example, make sure you have the following in place:

- You should have admin privilege to create a database in the given schema. To execute the following example you need to replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages** . Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
2. **Register the JDBC driver** . Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection** . Requires using the *DriverManager.getConnection()* method to create a Connection object, which represents a physical connection with database server.

To create a new database, you need not to give any database name while preparing database URL as mentioned in the below example.

4. **Execute a query** . Requires using an object of type Statement for building and submitting an SQL statement to the database.
5. **Clean up the environment** . Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:



Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
            Class.forName("com.mysql.jdbc.Driver");

            //STEP 3: Open a connection
            System.out.println("Connecting to database...");
            conn = DriverManager.getConnection(DB_URL, USER, PASS);

            //STEP 4: Execute a query
            System.out.println("Creating database...");
            stmt = conn.createStatement();

            String sql = "CREATE DATABASE STUDENTS";
            stmt.executeUpdate(sql);
            System.out.println("Database created successfully...");
        }catch(SQLException se){
            //Handle errors for JDBC
            se.printStackTrace();
        }catch(Exception e){
            //Handle errors for Class.forName
            e.printStackTrace();
        }finally{
            //finally block used to close resources
            try{
                if(stmt!=null)
                    stmt.close();
            }catch(SQLException se2){
            }// nothing we can do
            try{
                if(conn!=null)
                    conn.close();
            }catch(SQLException se){
                se.printStackTrace();
            }//end finally try
        }//end try
        System.out.println("Goodbye!");
    }//end main
} //end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to database...
Creating database...
Database created successfully...
Goodbye!
C:\>
```

JDBC - Select Database Example

This tutorial provides an example on how to select a Database using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you need to replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages** . Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
2. **Register the JDBC driver** . Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection** . Requires using the *DriverManager.getConnection()* method to create a Connection object, which represents a physical connection with a **selected** database.

Selection of database is made while you prepare database URL. Following example would make connection with **STUDENTS** database.

4. **Clean up the environment** . Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/STUDENTS";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        try{
```

```
//STEP 2: Register JDBC driver
Class.forName("com.mysql.jdbc.Driver");

//STEP 3: Open a connection
System.out.println("Connecting to a selected database...");
conn = DriverManager.getConnection(DB_URL, USER, PASS);
System.out.println("Connected database successfully...");
}catch(SQLException se){
    //Handle errors for JDBC
    se.printStackTrace();
}catch(Exception e){
    //Handle errors for Class.forName
    e.printStackTrace();
}finally{
    //finally block used to close resources
    try{
        if(conn!=null)
            conn.close();
    }catch(SQLException se){
        se.printStackTrace();
    }//end finally try
} //end try
System.out.println("Goodbye!");
} //end main
} //end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
Goodbye!
C:\>
```

JDBC - Drop Database Example

This tutorial provides an example on how to drop an existing Database using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you need to replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

NOTE: This is a serious operation and you have to make a firm decision before proceeding to delete a database because everything you have in your database would be lost.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using `import java.sql.*` will suffice.
2. **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection:** Requires using the `DriverManager.getConnection()` method to create a Connection object, which represents a physical connection with a database server.

Deleting a database does not require database name to be in your database URL. Following example would delete **STUDENTS** database.

4. **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to delete the database.
5. **Clean up the environment .** Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
            Class.forName("com.mysql.jdbc.Driver");

            //STEP 3: Open a connection
            System.out.println("Connecting to a selected database...");
            conn = DriverManager.getConnection(DB_URL, USER, PASS);
            System.out.println("Connected database successfully...");

            //STEP 4: Execute a query
            System.out.println("Deleting database...");
            stmt = conn.createStatement();

            String sql = "DROP DATABASE STUDENTS";
            stmt.executeUpdate(sql);
            System.out.println("Database deleted successfully...");
        }catch(SQLException se){
            //Handle errors for JDBC
            se.printStackTrace();
        }catch(Exception e){
            //Handle errors for Class.forName
            e.printStackTrace();
        }finally{
            //finally block used to close resources
```

```
try{
    if(stmt!=null)
        conn.close();
}catch(SQLException se){
} // do nothing
try{
    if(conn!=null)
        conn.close();
}catch(SQLException se){
    se.printStackTrace();
} //end finally try
} //end try
System.out.println("Goodbye!");
} //end main
} //end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
Deleting database...
Database deleted successfully...
Goodbye!
C:\>
```

JDBC - Create Tables Example

This tutorial provides an example on how to create a table using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you can replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using `import java.sql.*` will suffice.
2. **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection:** Requires using the `DriverManager.getConnection()` method to create a Connection object, which represents a physical connection with a database server.
4. **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to create a table in a selected database.
5. **Clean up the environment .** Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/STUDENTS";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
            Class.forName("com.mysql.jdbc.Driver");

            //STEP 3: Open a connection
            System.out.println("Connecting to a selected database...");
            conn = DriverManager.getConnection(DB_URL, USER, PASS);
            System.out.println("Connected database successfully...");

            //STEP 4: Execute a query
            System.out.println("Creating table in given database...");
            stmt = conn.createStatement();

            String sql = "CREATE TABLE REGISTRATION " +
                "(id INTEGER not NULL, " +
                " first VARCHAR(255), " +
                " last VARCHAR(255), " +
                " age INTEGER, " +
                " PRIMARY KEY ( id ))";

            stmt.executeUpdate(sql);
            System.out.println("Created table in given database...");
        }catch(SQLException se){
            //Handle errors for JDBC
            se.printStackTrace();
        }catch(Exception e){
            //Handle errors for Class.forName
            e.printStackTrace();
        }finally{
            //finally block used to close resources
            try{
                if(stmt!=null)
                    conn.close();
            }catch(SQLException se){
                //do nothing
            }try{
                if(conn!=null)
                    conn.close();
            }catch(SQLException se){
                se.printStackTrace();
            }
        }
    }
}
```

```
    }//end try
    System.out.println("Goodbye!");
} //end main
} //end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
Creating table in given database...
Created table in given database...
Goodbye!
C:\>
```

JDBC - Drop Tables Example

This tutorial provides an example on how to delete a table using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you can replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

NOTE: This is a serious operation and you have to make a firm decision before proceeding to delete a table because everything you have in your table would be lost.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
2. **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection:** Requires using the *DriverManager.getConnection()* method to create a Connection object, which represents a physical connection with a database server.
4. **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to drop a table in a selected database.
5. **Clean up the environment .** Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
```

```
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/STUDENTS";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
            Class.forName("com.mysql.jdbc.Driver");

            //STEP 3: Open a connection
            System.out.println("Connecting to a selected database...");
            conn = DriverManager.getConnection(DB_URL, USER, PASS);
            System.out.println("Connected database successfully...");

            //STEP 4: Execute a query
            System.out.println("Deleting table in given database...");
            stmt = conn.createStatement();

            String sql = "DROP TABLE REGISTRATION ";

            stmt.executeUpdate(sql);
            System.out.println("Table deleted in given database...");
        }catch(SQLException se){
            //Handle errors for JDBC
            se.printStackTrace();
        }catch(Exception e){
            //Handle errors for Class.forName
            e.printStackTrace();
        }finally{
            //finally block used to close resources
            try{
                if(stmt!=null)
                    conn.close();
            }catch(SQLException se){
                //do nothing
            }
            try{
                if(conn!=null)
                    conn.close();
            }catch(SQLException se){
                se.printStackTrace();
            }
            //end finally try
        }
        System.out.println("Goodbye!");
    }
}
//end main
//end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```




When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
Deleting table in given database...
Table deleted in given database...
Goodbye!
C:\>
```

JDBC - Insert Records Example

This tutorial provides an example on how to insert records in a table using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you can replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
2. **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection:** Requires using the *DriverManager.getConnection()* method to create a Connection object, which represents a physical connection with a database server.
4. **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to insert records into a table.
5. **Clean up the environment:** Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/STUDENTS";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
```

```
Class.forName("com.mysql.jdbc.Driver");

//STEP 3: Open a connection
System.out.println("Connecting to a selected database...");
conn = DriverManager.getConnection(DB_URL, USER, PASS);
System.out.println("Connected database successfully...");

//STEP 4: Execute a query
System.out.println("Inserting records into the table...");
stmt = conn.createStatement();

String sql = "INSERT INTO Registration " +
            "VALUES (100, 'Zara', 'Ali', 18)";
stmt.executeUpdate(sql);
sql = "INSERT INTO Registration " +
            "VALUES (101, 'Mahnaz', 'Fatma', 25)";
stmt.executeUpdate(sql);
sql = "INSERT INTO Registration " +
            "VALUES (102, 'Zaid', 'Khan', 30)";
stmt.executeUpdate(sql);
sql = "INSERT INTO Registration " +
            "VALUES (103, 'Sumit', 'Mittal', 28)";
stmt.executeUpdate(sql);
System.out.println("Inserted records into the table...");

}catch(SQLException se){
    //Handle errors for JDBC
    se.printStackTrace();
}catch(Exception e){
    //Handle errors for Class.forName
    e.printStackTrace();
}finally{
    //finally block used to close resources
    try{
        if(stmt!=null)
            conn.close();
    }catch(SQLException se){
    }// do nothing
    try{
        if(conn!=null)
            conn.close();
    }catch(SQLException se){
        se.printStackTrace();
    }//end finally try
} //end try
System.out.println("Goodbye!");
} //end main
} //end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
```

```
Inserting records into the table...
Inserted records into the table...
Goodbye!
C:\>
```

JDBC - Select Records Example

This tutorial provides an example on how to select/ fetch records from a table using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you can replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
2. **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection:** Requires using the *DriverManager.getConnection()* method to create a Connection object, which represents a physical connection with a database server.
4. **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to select (i.e. fetch) records from a table.
5. **Extract Data:** Once SQL query is executed, you can fetch records from the table.
6. **Clean up the environment:** Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/STUDENTS";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
            Class.forName("com.mysql.jdbc.Driver");

            //STEP 3: Open a connection
            System.out.println("Connecting to a selected database...");
```

```
conn = DriverManager.getConnection(DB_URL, USER, PASS);
System.out.println("Connected database successfully...");

//STEP 4: Execute a query
System.out.println("Creating statement...");
stmt = conn.createStatement();

String sql = "SELECT id, first, last, age FROM Registration";
ResultSet rs = stmt.executeQuery(sql);
//STEP 5: Extract data from result set
while(rs.next()){
    //Retrieve by column name
    int id = rs.getInt("id");
    int age = rs.getInt("age");
    String first = rs.getString("first");
    String last = rs.getString("last");

    //Display values
    System.out.print("ID: " + id);
    System.out.print(", Age: " + age);
    System.out.print(", First: " + first);
    System.out.println(", Last: " + last);
}
rs.close();
}catch(SQLException se){
    //Handle errors for JDBC
    se.printStackTrace();
}catch(Exception e){
    //Handle errors for Class.forName
    e.printStackTrace();
}finally{
    //finally block used to close resources
    try{
        if(stmt!=null)
            conn.close();
    }catch(SQLException se){
    }// do nothing
    try{
        if(conn!=null)
            conn.close();
    }catch(SQLException se){
        se.printStackTrace();
    }//end finally try
} //end try
System.out.println("Goodbye!");
} //end main
} //end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
Creating statement...
```

```
ID: 100, Age: 18, First: Zara, Last: Ali
ID: 101, Age: 25, First: Mahnaz, Last: Fatma
ID: 102, Age: 30, First: Zaid, Last: Khan
ID: 103, Age: 28, First: Sumit, Last: Mittal
Goodbye!
C:\>
```

JDBC - Update Records Example

This tutorial provides an example on how to update records in a table using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you can replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
2. **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection:** Requires using the *DriverManager.getConnection()* method to create a Connection object, which represents a physical connection with a database server.
4. **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to update records in a table. This Query makes use of **IN** and **WHERE** clause to update conditional records.
5. **Clean up the environment:** Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/STUDENTS";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
        Connection conn = null;
        Statement stmt = null;
        try{
            //STEP 2: Register JDBC driver
            Class.forName("com.mysql.jdbc.Driver");
```

```
//STEP 3: Open a connection
System.out.println("Connecting to a selected database...");
conn = DriverManager.getConnection(DB_URL, USER, PASS);
System.out.println("Connected database successfully...");

//STEP 4: Execute a query
System.out.println("Creating statement...");
stmt = conn.createStatement();
String sql = "UPDATE Registration " +
            "SET age = 30 WHERE id in (100, 101)";
stmt.executeUpdate(sql);

// Now you can extract all the records
// to see the updated records
sql = "SELECT id, first, last, age FROM Registration";
ResultSet rs = stmt.executeQuery(sql);

while(rs.next()){
    //Retrieve by column name
    int id = rs.getInt("id");
    int age = rs.getInt("age");
    String first = rs.getString("first");
    String last = rs.getString("last");

    //Display values
    System.out.print("ID: " + id);
    System.out.print(", Age: " + age);
    System.out.print(", First: " + first);
    System.out.println(", Last: " + last);
}
rs.close();
}catch(SQLException se){
    //Handle errors for JDBC
    se.printStackTrace();
}catch(Exception e){
    //Handle errors for Class.forName
    e.printStackTrace();
}finally{
    //finally block used to close resources
    try{
        if(stmt!=null)
            conn.close();
    }catch(SQLException se){
    }// do nothing
    try{
        if(conn!=null)
            conn.close();
    }catch(SQLException se){
        se.printStackTrace();
    }//end finally try
} //end try
System.out.println("Goodbye!");
} //end main
} //end JDBCExample
```

Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
Creating statement...
ID: 100, Age: 30, First: Zara, Last: Ali
ID: 101, Age: 30, First: Mahnaz, Last: Fatma
ID: 102, Age: 30, First: Zaid, Last: Khan
ID: 103, Age: 28, First: Sumit, Last: Mittal
Goodbye!
C:\>
```

JDBC - Delete Records Example

This tutorial provides an example on how to delete records from a table using JDBC application. Before executing following example, make sure you have the following in place:

- To execute the following example you can replace *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using is up and running.

Required Steps:

There are following steps required to create a new Database using JDBC application:

1. **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
2. **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
3. **Open a connection:** Requires using the *DriverManager.getConnection()* method to create a Connection object, which represents a physical connection with a database server.
4. **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to delete records from a table. This Query makes use of **WHERE** clause to delete conditional records.
5. **Clean up the environment:** Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code:

Copy and past following example in JDBCExample.java, compile and run as follows:

```
//STEP 1. Import required packages
import java.sql.*;

public class JDBCExample {
    // JDBC driver name and database URL
    static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
    static final String DB_URL = "jdbc:mysql://localhost/STUDENTS";

    // Database credentials
    static final String USER = "username";
    static final String PASS = "password";

    public static void main(String[] args) {
```

```
Connection conn = null;
Statement stmt = null;
try{
    //STEP 2: Register JDBC driver
    Class.forName("com.mysql.jdbc.Driver");

    //STEP 3: Open a connection
    System.out.println("Connecting to a selected database...");
    conn = DriverManager.getConnection(DB_URL, USER, PASS);
    System.out.println("Connected database successfully...");

    //STEP 4: Execute a query
    System.out.println("Creating statement...");
    stmt = conn.createStatement();
    String sql = "DELETE FROM Registration " +
        "WHERE id = 101";
    stmt.executeUpdate(sql);

    // Now you can extract all the records
    // to see the remaining records
    sql = "SELECT id, first, last, age FROM Registration";
    ResultSet rs = stmt.executeQuery(sql);

    while(rs.next()){
        //Retrieve by column name
        int id = rs.getInt("id");
        int age = rs.getInt("age");
        String first = rs.getString("first");
        String last = rs.getString("last");

        //Display values
        System.out.print("ID: " + id);
        System.out.print(", Age: " + age);
        System.out.print(", First: " + first);
        System.out.println(", Last: " + last);
    }
    rs.close();
}catch(SQLException se){
    //Handle errors for JDBC
    se.printStackTrace();
}catch(Exception e){
    //Handle errors for Class.forName
    e.printStackTrace();
}finally{
    //finally block used to close resources
    try{
        if(stmt!=null)
            conn.close();
    }catch(SQLException se){
        // do nothing
    }try{
        if(conn!=null)
            conn.close();
    }catch(SQLException se){
        se.printStackTrace();
    }//end finally try
} //end try
System.out.println("Goodbye!");
} //end main
} //end JDBCExample
```




Now let us compile above example as follows:

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces following result:

```
C:\>java JDBCExample
Connecting to a selected database...
Connected database successfully...
Creating statement...
ID: 100, Age: 30, First: Zara, Last: Ali
ID: 102, Age: 30, First: Zaid, Last: Khan
ID: 103, Age: 28, First: Sumit, Last: Mittal
Goodbye!
C:\>
```

JDBC - Batch Processing:

Batch Processing allows you to group related SQL statements into a batch and submit them with one call to the database.

When you send several SQL statements to the database at once, you reduce the amount of communication overhead, thereby improving performance.

- JDBC drivers are not required to support this feature. You should use the *DatabaseMetaData.supportsBatchUpdates()* method to determine if the target database supports batch update processing. The method returns true if your JDBC driver supports this feature.
- The **addBatch()** method of *Statement*, *PreparedStatement*, and *CallableStatement* is used to add individual statements to the batch. The **executeBatch()** is used to start the execution of all the statements grouped together.
- The **executeBatch()** returns an array of integers, and each element of the array represents the update count for the respective update statement.
- Just as you can add statements to a batch for processing, you can remove them with the **clearBatch()** method. This method removes all the statements you added with the **addBatch()** method. However, you cannot selectively choose which statement to remove.

JDBC - Streaming Data:

A *PreparedStatement* object has the ability to use input and output streams to supply parameter data. This enables you to place entire files into database columns that can hold large values, such as CLOB and BLOB data types.

There are following methods which can be used to stream data:

1. **setAsciiStream():** This method is used to supply large ASCII values.
2. **setCharacterStream():** This method is used to supply large UNICODE values.
3. **setBinaryStream():** This method is used to supply large binary values.

The *setXXXStream()* method requires an extra parameter, the file size, besides the parameter placeholder. This parameter informs the driver how much data should be sent to the database using the stream.

Further Detail:



Refer to the link <http://www.tutorialspoint.com/jdbc>

List of Tutorials from **TutorialsPoint.com**

- | | |
|---|---|
| <ul style="list-style-type: none">▪ Learn JSP▪ Learn Servlets▪ Learn log4j▪ Learn iBATIS▪ Learn Java▪ Learn JDBC▪ Java Examples▪ Learn Best Practices▪ Learn Python▪ Learn Ruby▪ Learn Ruby on Rails▪ Learn SQL▪ Learn MySQL▪ Learn AJAX▪ Learn C Programming▪ Learn C++ Programming▪ Learn CGI with PERL▪ Learn DLL▪ Learn ebXML▪ Learn Euphoria▪ Learn GDB Debugger▪ Learn Makefile▪ Learn Parrot▪ Learn Perl Script▪ Learn PHP Script▪ Learn Six Sigma▪ Learn SEI CMMI▪ Learn WiMAX▪ Learn Telecom Billing | <ul style="list-style-type: none">▪ Learn ASP.Net▪ Learn HTML▪ Learn HTML5▪ Learn XHTML▪ Learn CSS▪ Learn HTTP▪ Learn JavaScript▪ Learn jQuery▪ Learn Prototype▪ Learn script.aculo.us▪ Web Developer's Guide▪ Learn RADIUS▪ Learn RSS▪ Learn SEO Techniques▪ Learn SOAP▪ Learn UDDI▪ Learn Unix Sockets▪ Learn Web Services▪ Learn XML-RPC▪ Learn UML▪ Learn UNIX▪ Learn WSDL▪ Learn i-Mode▪ Learn GPRS▪ Learn GSM▪ Learn WAP▪ Learn WML▪ Learn Wi-Fi |
|---|---|

webmaster@TutorialsPoint.com

